

AD340

Parallel and Semi
Serial Open Loop
Integrated Solution

Feature :

- AD340 is the Open loop integrated solution for elevator with ACIM (Geared) Motor Only.
- No Feedback Device like Encoder and PG Card Require, Saving Cost.
- High Safety with Great Riding comfort.
- Flexible emergency backup power; 220 Vac power input makes emergency evacuation easy with automatic light load direction search
- Handheld Keypad operation tools make easy commissioning.
- 20 fault codes to facilitate easy diagnostics.
- Auto and Manual Door Supported.
- Flexible programmable I/O's.
- Static auto tuning for asynchronous machines (without brake opening)

AD340 : No of Floor

- Full Parallel :
 - Button input and indicator output: standard 12 Stop With Extension
 - All Button Input Output are Programmable.
- Semi Serial :
 - All Car Related Information through CAN bus Card AD-CTB & AD-CCB.
 - Landing Call Will be on board: 16 Stop Down Collective, 8 Stop Full Collective.
 - All Button Input Output are Programmable.

Power Rating

- 3.7KW to 30KW,
Three-Phase (3 - Ø)
380 to 480Vac



Applications

- Simplex and Duplex Only,
- Medium speed, low speed.
- Commercial elevator, passenger elevator, disabled elevator etc.,
- AD340 Elevator rated speed ≤ 0.8 m/sec.